



Declaration of Performance

011-BEW-2020/03/25

Unique identification code of the product-type:

BEWiSynbra XPS 300, BEWiSynbra XPS 300PP, BEWiSynbra XPS 300 U, BEWiSynbra XPS 300 PPU

Intended use:

Thermal insulation for buildings

Manufacturer:

BEWi M-Plast Oy, P.O.Box 360 FI-06101 PORVOO, www.bewisynbra.com

System of AVCP:

AVCP 3

Harmonised standard:

EN 13164:2012 + A1:2015

Notified bodies:

Eurofins Expert Services (nb. 0809) and Vilnius Gediminas Technical University (nb. 1688)

Declared performance:

Essential characteristics	Performance		
Reaction to fire	Reaction to fire		F
Water permeability	Long term water absorption after total immersion	Thickness ≤ 20 mm	NPD
		Thickness ≥ 30 mm	WL(T)0,7
	Long term water absorption after diffusion	Thickness ≤ 20 mm	NPD
		Thickness ≥ 30 mm	WD(V)2
Tolerances of length, width, squareness, flatness and thickness		Nominal length or width mm	
	Length or width mm	l or b ≤ 1500 mm	± 8
		l or b > 1500 mm	± 10
	Squareness mm/m	l or b ≤ 1500 mm	5
		l or b > 1500 mm	5
	Flatness mm/m	l or b ≤ 1500 mm	6
l or b > 1500 mm		6	
Thickness tolerance		T1	
Thermal resistance	Thickness	Thermal conductivity	Thermal resistance R _D
	15	λ _D = 0,035	0,4
	20	λ _D = 0,035	0,55
	30	λ _D = 0,034	0,85
	40	λ _D = 0,035	1,1
	50	λ _D = 0,035	1,4
	60	λ _D = 0,035	1,7
	70	λ _D = 0,037	1,85
	80	λ _D = 0,037	2,15
	100	λ _D = 0,037	2,7
Compressive strength	Compressive stress or strength	thickness ≤ 40 mm	CS(10\Y)250
		thickness ≥ 50 mm	CS(10\Y)300
Dimensional stability under specified temperature and humidity conditions	Durability characteristics		DS(70,90)
Durability of compressive strength against ageing and degradation	Compressive creep ≥ 50 mm		CC(3,5/2,5/50)135
	Freeze-thaw resistance ≥ 30 mm		FTCD2

Harmonized technical specification EN 13164:2012 + A1:2015

NPD = No Performance Determined

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Jouni Jokela, Production manager

Porvoo 25.03.2020



Jouni Jokela